

XIBU SENSOR TAPS

EFFICIENT AND ECONOMICAL

- Automatic hygienic rinse
- Prevents the transmission of germs
- Protects from vandalism
- Water & energy efficient





XIBU SENSOR TAPS

The Xibu sensor tap range are efficient, economical, hygienic, safe, comfortable and convenient. The sensor taps allow water to be available whenever it is needed and inhibits any unnecessary water consumption with need orientated technology. The transmission of germs is also prevented while the robust all-metal design aids in protection from vandalism. The standardised parts makes for quick and cost effective servicing and repairs.



WATER IS PRECIOUS

Our "blue planet" is covered to 71% with water. Though, only 3.5% is fresh water and only a fraction, around 0.3%, is available as drinking water. We better be very careful with our resources!





SPECIFICATIONS

Finish Chrome, Matte

PowerDC 6V Battery or 240V ACWater Pressure0.03-0.8MPA (0.3-8 bar)

Flow Rate 4 L / min

Connection 3/8" Stainless Steel hose

Safety Shut Off 1 minute

Sensing PIR – Automatic range adjustment

DIMENSIONS

Height 190mm, depth 165mm, hole Ø 33mm Nosing 130mm, discharge height 128mm



PROFI inox



SPECIFICATIONS

Finish Stainless Steel

Power DC 6V Battery or 240V AC **Water Pressure** 0.03-0.8MPA (0.3-8 bar)

Flow Rate 4 L / min

Connection 3/8" Stainless Steel hose

Safety Shut Off 1 minute

Sensing PIR – Automatic range adjustment

DIMENSIONS

Height 165mm, depth 162mm, hole \emptyset 34mm Nosing 120mm, discharge height 130mm

Xibu SMART Chrome



SPECIFICATIONS

Finish Chrome

Power DC 6V Battery or 240V AC **Water Pressure** 0.03-0.8MPA (0.3-8 bar)

Flow Rate 4 L / min

Connection 3/8" Stainless Steel hose

Safety Shut Off 1 minute

Sensing PIR – Automatic range adjustment

DIMENSIONS

Height 150mm, depth 145mm, hole Ø 34-38mm Nosing 110mm, discharge height 110mm



Xibu BISTRO Chrome



SPECIFICATIONS

Finish Chrome

Power DC 6V Battery or 240V AC **Water Pressure** 0.03-0.8MPA (0.3-8 bar)

Flow Rate 4 L / min

Connection 3/8" Stainless Steel hose

Safety Shut Off 1 minute

Sensing PIR – Automatic range adjustment

DIMENSIONS

Height 250mm, depth 286mm, hole Ø 34mm Nosing 245mm, discharge height 175mm

Xibu LAB Chrome



SPECIFICATIONS

Finish Chrome

Power DC 6V Battery or 240V AC Water Pressure 0.03-0.8MPA (0.3-8 bar)

Flow Rate 4 L / min

Connection 3/8" Stainless Steel hose

Safety Shut Off 1 minute

Sensing PIR – Automatic range adjustment

DIMENSIONS

Height 265mm, depth 233mm, hole Ø 34mm Nosing 175mm, discharge height 160mm